

IT 400 - Technische Daten



Description

IT 400 ist ein Reifen mit Rippenmuster zum vorwiegenden Einsatz auf der Straße für Tieflader in Transportanwendungen. Der Reifen eignet sich für Hochgeschwindigkeitsanwendungen und bietet deutliche Kraftstoffersparnis.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Tieflader

Version	STANDARD
Type	TT
Tyre Size	10.00 - 15
LI/SS	143/138 J

Dimensions US Standard

Usa code	94008261
Ply Rating	18
Section Width (inch)	10.8
Overall Diameter (inch)	36.4
Static Loaded Radius (inch)	16.1
Rolling Circumference (inch)	108.1
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
ECE	E11-54R-0019537

Load capacity (lbs)

mph / psi	140	130	115
10	9940	-	-
20	-	8020	-
62 LS	-	6060	-
62 LD	-	-	5310

Printed on 23.04.2024 10:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..