

## IT 400 - Technische Daten



### Description

IT 400 ist ein Reifen mit Rippenmuster zum vorwiegenden Einsatz auf der Straße für Tieflader in Transportanwendungen. Der Reifen eignet sich für Hochgeschwindigkeitsanwendungen und bietet deutliche Kraftstoffersparnis.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industrie: Tieflader

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15
LI/SS	125/121 J

## Dimensions US Standard

Usa code	94008278
Ply Rating	16
Section Width (inch)	8.3
Overall Diameter (inch)	31.3
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	93
Rim Rec	6.0
Rim Alt	5.50 F ; 6.50
ECE	E11-54R-0019535

## Load capacity (lbs)

mph / psi	125	115
62 LS	3650	-
62 LD	-	3210

Printed on 23.04.2024 09:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..