

JUMBO TRAX HD - Technische Daten



Description

JUMBO TRAX HD ist ein Reifen mit Blockprofil für Skid-Steer-Lader. Er zeichnet sich durch besondere Schnitt- und Reißfestigkeit und eignet sich vortrefflich für schwere Betriebsbedingungen. Diese tiefe Lauffläche kombiniert mit dem ausgezeichneten Flankenschutz bewirkt einen verlängerten Produktlebenszyklus. JUMBO TRAX HD ist auch in Ausführung "special" erhältlich.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Skid-Steer-Lader

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	325
Overall Diameter (mm)	855
Static Loaded Radius (mm)	387
Rolling Circumference (mm)	2522
Rim Rec	9.75
ECE	E11-106R-005563

Load capacity (Kg)

	km/h / bar	4.50
	10	2540
	15	2005
	25	1855

Printed on 27.04.2024 09:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..