

## LG 306 - Technische Daten



### Description

LG 306 ist ein Reifen für Rasenflächen und Anwendungen im Gartenbau, der sich für Rasenmäher eignet. In einigen Größen ist LG 306 auch mit Kleintraktoren einzusetzen. Durch das spezielle Laufflächenmuster ist der Reifen sanft zu dem Boden und gleichzeitig leicht manövrierbar. LG 306 ist in Ausführung "aramid-belted" mit Aramidbändern erhältlich für Nutzer, die erhöhte Durchstichfestigkeit benötigen.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Rasenmäher • Kleintraktor

|           |                 |
|-----------|-----------------|
| Version   | STANDARD        |
| Type      | TL              |
| Tyre Size | 20 X 10.00 - 10 |

## Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94012435        |
| Ply Rating                   | 4               |
| Section Width (inch)         | 9.8             |
| Overall Diameter (inch)      | 20              |
| Static Loaded Radius (inch)  | 8.9             |
| Rolling Circumference (inch) | 58              |
| Rim Rec                      | 8.00 I - 55     |
| Rim Alt                      | 7.00 I - 55     |
| ECE                          | E11-106R-003453 |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 22   |
| 10        | 1170 |

Printed on 26.04.2024 23:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..