

LG 408 - Technische Daten



Description

LG 408 ist ein Reifen für Rasenflächen und Anwendungen im Gartenbau, der sich für Rasenmäher und Kleintraktoren eignet. Durch das spezielle Laufflächenmuster ist der Reifen sanft zu dem Boden und vermeidet Rasenschäden. LG 408 ist in Ausführung "aramid-belted" mit Aramidbändern erhältlich für Nutzer, die erhöhte Durchstichfestigkeit benötigen.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Rasenmäher • Kleintraktor

Version	STANDARD
Type	TL
Tyre Size	26.5 X 14.00 - 12

Dimensions US Standard

Usa code	94012886
Ply Rating	4
Section Width (inch)	15
Overall Diameter (inch)	26.2
Static Loaded Radius (inch)	11.5
Rolling Circumference (inch)	75.9
Rim Rec	12.00 I
ECE	E11-106R-005205

Load capacity (lbs)

mph / psi	18
10	2170

Printed on 26.04.2024 07:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..