

## LG RIB - Technische Daten



### Description

LG RIB ist ein Reifen für Rasenflächen und Anwendungen im Gartenbau, der sich für Rasenmäher und Kleintraktoren eignet. Durch das spezielle Laufflächenmuster ist der Reifen sanft zu dem Boden und erleichtert gleichzeitig das Handling. LG RIB ist in Ausführung "aramid-belted" mit Aramidbändern erhältlich für Nutzer, die erhöhte Durchstichfestigkeit benötigen.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Rasenmäher • Kleintraktor

Version	STANDARD
Type	TL
Tyre Size	16 X 6.50 - 8

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	170
Overall Diameter (mm)	408
Static Loaded Radius (mm)	182
Rolling Circumference (mm)	1183
Rim Rec	5.375 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-003468

## Load capacity (Kg)

km/h / bar	2.90
15	355

Printed on 17.04.2024 03:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..