

LOADER SPECIAL - Technische Daten



Description

LOADER SPECIAL (L-5) ist ein Diagonalreifen, der ihre Lader in Bewegung hält und dabei mit erstklassiger Effizienz bei harten Betriebsbedingungen auf felsigem Gelände glänzt. Optimale Traktion und hervorragende Schnitffestigkeit geben ihrer Produktivität Auftrieb.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Planierer • Radlader

Version	STANDARD
Type	TL
Tyre Size	29.5 - 25

Dimensions International Standard

Ply Rating	32
Overall Width (mm)	770
Overall Diameter (mm)	1930
Static Loaded Radius (mm)	884
Rolling Circumference (mm)	5753
Rim Rec	25.00/3.5
TRA Code	L5

Load capacity (Kg)

km/h / bar	5.00
10	19250

Printed on 25.04.2024 19:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..