

## LP 450 - Technische Daten



### Description

LP 450 ist ein Reifen zum vorwiegenden Einsatz auf der Straße für Tieflader in Transportanwendungen. Dieser Hochgeschwindigkeitsreifen bewirkt deutliche Kraftstoffersparnis sowie einen verlängerten Produktlebenszyklus.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Tieflader

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

## Dimensions International Standard

<b>Ply Rating</b>	12
<b>Section Width (mm)</b>	214
<b>Overall Diameter (mm)</b>	710
<b>Static Loaded Radius (mm)</b>	321
<b>Rolling Circumference (mm)</b>	2109
<b>Rim Rec</b>	6.00 MH

## Load capacity (Kg)

	km/h / bar	6.90
	100 LS	1285
	100 LD	1130

Printed on 26.04.2024 17:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..