

MAGLIFT ECO - Technische Daten



Description

MAGLIFT ECO wurde speziell für Anwendungen mit Gabelstaplern entwickelt. Der Reifen besteht mit maximaler Stabilität und optimierter Gewichtsverteilung der Lasten. Die verstärkte Reifenstruktur vermeidet das Risiko von Reifenschlupf, während der speziell entworfene Felgenschutz vor Radschäden bewahrt. MAGLIFT ECO weist hervorragende Traktion auf und bietet einen geringen Rollwiderstand bei niedriger Hitzebildung für verbesserte Effizienz.

UM

US Standard

Construction

◆ SOLID

Machinery

Industrie: Gabelstapler

Version

LIP

Type

Tyre Size

15 X 4.5 - 8
(125 / 75 - 8)

Dimensions US Standard

Usa code	94065417
Section Width (inch)	4.3
Overall Diameter (inch)	14.9
Rim Rec	3.00 D - 8

Load capacity (lbs)

	mph / psi	-
15 LOAD WHEEL		2290
15 STEER WHEEL		1765

Printed on 26.04.2024 09:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..