

MAGLIFT PREMIUM - Technische Daten



Description

MAGLIFT PREMIUM ist ein Vollreifen, der speziell für schweren Einsatz mit Gabelstaplern in Hafenanwendungen, im Bergbau oder auf Schrottplätzen entwickelt wurde. Das extra tiefe Laufflächenprofil (25% mehr im Vergleich zur Standardversion) mit seinem aggressiven und robusten Muster verleiht hervorragende Seitentraktion und in vordere Zugrichtung neben ausgezeichneter Lenkkontrolle. Die einzigartige Gummimischung der Lauffläche gewährleistet hohe Schnitt- und Reißfestigkeit und somit einen verlängerten Produktlebenszyklus. Weitere Vorteile sind der niedrige Rollwiderstand sowie ein ruhiger Lauf.

UM

International Standard

Construction

◆ SOLID

Machinery

Industrie: Gabelstapler

Version

LIP

Type

Tyre Size

6.50 - 10

Dimensions International Standard

Section Width (mm)	150
Overall Diameter (mm)	582
Rim Rec	5.00 F - 10

Load capacity (Kg)

	km/h / bar	-
25 LOAD WHEEL		2340
25 STEER WHEEL		1800

Printed on 25.04.2024 16:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..