MH TR 182 - Technische Daten

Description

MH TR 182 eignet sich für Fahrzeuge zur Beförderung von Mobilheimen. Der für den Straßeneinsatz vorgesehene Hochgeschwindigkeitsreifen senkt deutlich den Kraftstoffverbrauch. MH TR bietet Beständigkeit und starke Leistung während des gesamten Produktlebenszyklus.

UM

US Standard

Construction

BIAS

Machinery

Landwirtschaft: Mobilheim

Version	STANDARD
Type	TL
Tyre Size	8 - 14.5

Dimensions US Standard

Usa code	94008599
Ply Rating	12
Section Width (inch)	8.1
Overall Diameter (inch)	28
Rim Rec	6.00 MH

Load capacity (lbs)

mph / psi	100
62	2835

Printed on 24.04.2024 12:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..