

MINE STAR - Technische Daten



Description

MINE STAR ist ein Diagonalreifen, der sich als erstklassige Wahl bei schweren Einsatzbedingungen im Bergbau erweist. Der Reifen zeichnet sich durch hohe Widerstandsfähigkeit gegenüber Schnitten/Rissen und Durchstößen aus, wodurch die Leistungsfähigkeit optimiert wird.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Untertagefahrzeug

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 55 X 19.00 - 25 |

Dimensions US Standard

| | |
|------------------------------|----------|
| Usa code | 94067879 |
| Ply Rating | 50 |
| Section Width (inch) | 18.9 |
| Overall Diameter (inch) | 55.1 |
| Static Loaded Radius (inch) | 24.9 |
| Rolling Circumference (inch) | 168.5 |
| Rim Rec | 14.00 |
| TRA Code | L5 |

Load capacity (lbs)

| mph / psi | 145 |
|-----------|-------|
| 3 | 38100 |
| 5 | 33800 |
| 10 | 31400 |
| 15 | 28700 |

Printed on 19.04.2024 23:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..