

MINE STAR - Technische Daten



Description

MINE STAR ist ein Diagonalreifen, der sich als erstklassige Wahl bei schweren Einsatzbedingungen im Bergbau erweist. Der Reifen zeichnet sich durch hohe Widerstandsfähigkeit gegenüber Schnitten/Rissen und Durchstößen aus, wodurch die Leistungsfähigkeit optimiert wird.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Untertagefahrzeug

Version	STANDARD
Type	TT
Tyre Size	8.25 - 15

Dimensions International Standard

Ply Rating	20
Section Width (mm)	244
Overall Diameter (mm)	848
Rim Rec	6.5
Rim Alt	6.0 ; 7.0

Load capacity (Kg)

km/h / bar	9.30
25	3790

Printed on 02.12.2023 02:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..