

## MINEFORCE - Technische Daten



### Description

Der MINEFORCE ist ein Diagonalreifen, der speziell für Muldenkipper im Bergbau und in Steinbrüchen entwickelt wurde. Der MINEFORCE Hochleistungs-Muldenkipperreifen ist die innovative Antwort von BKT auf felsige, abrasive und raue Bergbauumgebungen. Er besitzt ein einzigartiges Profildesign mit speziell entwickelten Laufflächenmischungen für harte, felsige und schwierige Bergbaubedingungen. Seine große Aufstandsfläche mit starren Stollen sorgt für gleichmäßigen Profilabrieb und eine längere Lebensdauer.

### UM

US Standard

### Construction

 BIAS

### Machinery

OTR: Starrer Muldenkipper

Version	STANDARD
Type	TL
Tyre Size	27.00 - 49

## Dimensions US Standard

Usa code	94069064
Ply Rating	54
TMPH	325
Overall Width (inch)	29.1
Overall Diameter (inch)	106.1
Static Loaded Radius (inch)	49.3
Rolling Circumference (inch)	314.4
Rim Rec	19.50/4.0
TRA Code	E4

## Load capacity (lbs)

mph / psi	94	127
30	60000	-
5	-	103500

Printed on 30.09.2023 04:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..