

## MP 567 - Technische Daten



### Description

MP 567 ist ein agro-industrieller Reifen für Feld- und Straßentransport sowie Anwendungen im Bereich Gemeindearbeiten/Wartung. Es ist der perfekte Reifen für Teleskoplader und landwirtschaftliche Geräte. Der MP 567 Reifen steht für gute Traktion bei jedem Wetter sowie ausgezeichnete Selbstreinigungseigenschaften. Der Reifen bietet außerdem ein komfortables Fahrerlebnis neben einem längeren Reifenleben.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Teleskoplader  
Industrie: Teleskoplader • Universelles Fahrzeug

Version	IMPLEMENT
Type	TL
Tyre Size	11.5/80 - 15.3
LI/SS DRIVE WHEEL	126 A8
LI/SS FREE ROLLING	139 A8

## Dimensions US Standard

Usa code	94057597
Ply Rating	14
TMPH	1
Section Width (inch)	11.5
Overall Diameter (inch)	34.2
Static Loaded Radius (inch)	15.5
Rolling Circumference (inch)	101.5
Rim Rec	9.0
ECE	E11-106R-003373

## Load capacity (lbs)

mph / psi	69
25 FR	5350
25 DW	3750

Printed on 26.04.2024 06:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..