

MP 570 - Technische Daten



Description

MP 570 ist ein agro-industrieller Reifen für Bagger und Baggerlader. Dieser Reifen verleiht gute Traktion und Beständigkeit sowie ausgezeichnete Selbstreinigungseigenschaften bei jeglichen Einsatzbedingungen.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Baggerlader

Industrie: Baggerlader • Bagger • Universelles Fahrzeug

Version	STANDARD
Type	TL
Tyre Size	12.5 - 18

Dimensions International Standard

Ply Rating	10
Section Width (mm)	308
Overall Diameter (mm)	990
Static Loaded Radius (mm)	450
Rolling Circumference (mm)	2950
Rim Rec	11
Rim Alt	12 SDC
ECE	E4-54R-0022629

Load capacity (Kg)

km/h / bar	3.00
80	1930
50	2000

Printed on 18.04.2024 04:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..