

MP 585 - Technische Daten



Description

MP 585 ist ein agro-industrieller Reifen, der sich für Anwendungen mit Mehrzweckfahrzeugen im Bereich Gemeindearbeiten/Wartung eignet. Dieser Reifen wurde mit einem speziellen Blockmuster entwickelt, das maximale Stabilität und Beständigkeit unter schwierigsten Einsatzbedingungen auch bei hohen Geschwindigkeiten bietet.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Universelles Fahrzeug

Industrie: Universelles Fahrzeug

Version	STANDARD
Type	TT
Tyre Size	6.50 - 20
LI/SS	106 A6

Dimensions International Standard

Ply Rating	10
Section Width (mm)	200
Overall Diameter (mm)	875
Rim Rec	5.50 F
Rim Alt	4.00 E ; 5.00 F
ECE	E11-106R-004308

Load capacity (Kg)

km/h / bar	5.50
30	950

Printed on 27.04.2024 04:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..