

MT 612 - Technische Daten



Description

MT 612 wurde speziell für den vielseitigen Einsatz auf und abseits der Straße entworfen. Die robuste Karkasse ermöglicht die Beförderung schwerer Lasten bei hoher Geschwindigkeit, während die breiten Stollen erstklassige Traktion bieten. Die extra breite Lauffläche bewirkt ausgezeichnete Flotation auf Sand und Schlamm.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Anhänger

Industrie: Universelles Fahrzeug

Version	STANDARD
Type	TT
Tyre Size	14.00 - 20

Dimensions US Standard

Usa code	94029433
Ply Rating	20
Section Width (inch)	15.4
Overall Diameter (inch)	49.8
Static Loaded Radius (inch)	23.4
Rolling Circumference (inch)	150.7
Rim Rec	10
ECE	E11-54R-0021125

Load capacity (lbs)

mph / psi	110
50 LS	10750
50 LD	9640

Printed on 26.04.2024 04:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..