

MT 612 - Datenblatt



Description

MT 612 wurde speziell für den vielseitigen Einsatz auf und abseits der Straße entworfen. Die robuste Karkasse ermöglicht die Beförderung schwerer Lasten bei hoher Geschwindigkeit, während die breiten Stollen erstklassige Traktion bieten. Die extra breite Lauffläche bewirkt ausgezeichnete Flotation auf Sand und Schlamm.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Anhänger

Industrie: Universelles Fahrzeug

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
14.00 - 20	STANDARD	18	10		390	1265	594	3827	TT	
14.00 - 20	STANDARD	22	10		390	1265	594	3827	TT	
14.00 - 20	STANDARD	20	10		390	1265	594	3827	TT	E11-54R-0021125
16.0/70 - 20	STANDARD	16	13.00 T		405	1095	520	3327	TT	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05.11.2024 07:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..