

MULTI RIB - Technische Daten



Description

MULTI RIB ist ein agro-industrieller Reifen für die Bodenbearbeitung und Transportanwendungen mit 2WD Traktoren und landwirtschaftlichen Geräten. Er bietet ausgezeichnete Manövrierbarkeit während des langen Produktlebenszyklus. Er ist in unterschiedlichen Ausführungen für jeden Bedarf erhältlich: Eine „aramid belted“ Version mit Aramidbändern für verbesserte Durchstichfestigkeit sowie eine „HD“-Ausführung mit besonders schnitt- und reißfester Gummimischung.

UM

International Standard

Construction

❖ BIAS

Machinery

Landwirtschaft: 2WD-Traktor • Landwirtschaftliche Geräte

Version	HD
Type	TL
Tyre Size	11.00 - 16

Dimensions International Standard

Ply Rating	12
Section Width (mm)	315
Overall Diameter (mm)	930
Rim Rec	W10 L
Rim Alt	W 8 ; W 8 L

Load capacity (Kg)

km/h / bar	4.10
40	1550

Printed on 23.04.2024 18:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..