

## MULTIMAX MP 519 - Technische Daten



### Description

Der MULTIMAX MP 519 Reifen eignet sich besonders für Leicht-LKWs in allen Transportanwendungen. Die mit Stahlgürteln verstärkte Karkasse steht für hervorragende Stabilität bei hohen Geschwindigkeiten (90 km/h). Dank des geringen Rollwiderstandes bietet der Reifen einen reduzierten Kraftstoffverbrauch.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industrie: Leicht-Lkw

Version	STANDARD
Type	TL
Tyre Size	7.50 R 16 LT
LI/SS	109/107 G

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	220
Overall Diameter (mm)	810
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2449
Rim Rec	6.00
Rim Alt	5.50 F ; 6 L ; 7 L

## Load capacity (Kg)

	km/h / bar	3.5
	90 LS	1030
	90 LD	975

Printed on 26.04.2024 23:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..