

MULTIMAX MP 519 - Datenblatt



Description

Der MULTIMAX MP 519 Reifen eignet sich besonders für Leicht-LKWs in allen Transportanwendungen. Die mit Stahlgürteln verstärkte Karkasse steht für hervorragende Stabilität bei hohen Geschwindigkeiten (90 km/h). Dank des geringen Rollwiderstandes bietet der Reifen einen reduzierten Kraftstoffverbrauch.

UM

US Standard

Construction

 RADIAL

Machinery

Industrie: Leicht-Lkw

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
7.50 R 16 LT	STANDARD	94053384	109/107 G	6	6.00	5.50 F ; 6 L ; 7 L	8.7	31.9	14.8	96.4	TL	
7.50 R 16 LT	STANDARD	94063437	112/110G	8	6.00	5.50 F ; 6 L ; 7 L	8.7	31.9	14.8	96.4	TL	E11-54R-0019046

Printed on 26.04.2024 17:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..