

MULTIMAX MP 522 - Datenblatt



Description

MULTIMAX MP 522 ist BKTs Mehrzweckreifen für agro-industrielle Anwendungen. Er eignet sich für alle Bagger- und Ladearbeiten mit Fahrzeugen wie Teleskopladern und Kompaktladern. Stabilität und hohe Traktion sind seine Stärken neben erstklassiger Durchstichfestigkeit. Dank der speziellen Gummimischung ist MULTIMAX MP 522 außergewöhnlich widerstandsfähig gegenüber Schnitten und Rissen.

UM

International Standard

Construction

 RADIAL

Machinery

Landwirtschaft: Kompaktlader • Teleskoplader
Industrie: Kompaktlader • Teleskoplader

| SIZE | Version | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|---|----------|----------|--------------------|--|-----|------|-----|------|-----|------|-----------------|
| 280/80 R 18 IND (10.5/80 R 18) | STANDARD | 132 A8/B | W 9 ; 9 ; 9 SDC | W 8 ; W 10 | 282 | 907 | 421 | 2748 | 425 | TL | E11-106R-002962 |
| 340/80 R 18 IND (12.5/80 R 18) | STANDARD | 143 A8/B | 11 ; 11 SDC ; W 11 | W 10 ; 12 ; 12 SDC | 343 | 1006 | 458 | 3023 | 475 | TL | E4-106R-002654 |
| 340/80 R 20 IND | STANDARD | 144 A8/B | 11 | W10 ; 11 SDC ; W11 ; 12 ; 12 SDC | 343 | 1052 | 481 | 3212 | 500 | TL | E11-106R-002969 |
| 380/75 R 20 IND (14.5 R 20) | STANDARD | 148 A8/B | W 12 | W 11 ; 11 ; 12 | 384 | 1074 | 483 | 3251 | 500 | TL | E11-106R-002963 |
| 400/70 R 20 IND (16.0/70 R 20) | STANDARD | 149 A8/B | 13 | 12 SDC ; 13 SDC ; 14 | 404 | 1068 | 476 | 3222 | 525 | TL | E4-106R-002319 |
| 400/70 R 24 IND | STANDARD | 152 A8/B | 13 | DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L | 404 | 1170 | 533 | 3527 | 575 | TL | E11-106R-002964 |
| 400/80 R 24 IND (16.0/80 R 24) | STANDARD | 162 A8/B | DW 13 | DW 12 ; DW 13 L ; DW 14 L | 404 | 1250 | 553 | 3778 | 600 | TL | E11-106R-002965 |
| 440/80 R 24 IND | STANDARD | 161 A8/B | DW 14 L | DW 13 ; DW 13 L ; DW 15 L | 441 | 1314 | 586 | 3958 | 625 | TL | E11-106R-002966 |
| 460/70 R 24 IND (17.5L R 24) | STANDARD | 159 A8/B | DW 15 L | DW 14 L ; DW 16 L | 465 | 1250 | 568 | 3766 | 600 | TL | E4-106R-002396 |
| 500/70 R 24 IND (19.5L R 24) | STANDARD | 164 A8/B | DW 16 L | DW 15 L ; DW 18 L | 503 | 1310 | 595 | 3940 | 625 | TL | E4-106R-002395 |
| 540/70 R 24 IND | STANDARD | 168 A8/B | DW 16 L | DW 18 L | 530 | 1366 | 611 | 4133 | 650 | TL | E11-106R-002967 |
| 480/80 R 26 IND | STANDARD | 160 A8/B | DW 15 L | DW 16 L | 479 | 1428 | 638 | 4287 | 675 | TL | E11-106R-002970 |
| 480/80 R 26 IND | STANDARD | 167 A8/B | DW 15 L | DW 16 L | 479 | 1428 | 638 | 4287 | 675 | TL | E11-106R-008146 |
| 440/80 R 28 IND | STANDARD | 156 A8/B | DW 14 L | DW 13 ; DW 13 L ; DW 15 L | 441 | 1415 | 643 | 4278 | 675 | TL | E11-106R-002968 |

Printed on 14.04.2024 06:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..