

## MULTIMAX MP 540 - Technische Daten



### Description

Der MULTIMAX MP 540 wurde von BKT für alle Mehrzweckfahrzeuge entwickelt. Dank des Vollstahlgehäuses ist der MULTIMAX MP 540 in der Lage, bei Straßen- und Geländeeinsätzen schwere Lasten zu bewältigen. Darüber hinaus bietet sein Blockprofil-Design eine hervorragende Stabilität und Haltbarkeit.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Landwirtschaft: Universelles Fahrzeug  
Industrie: Universelles Fahrzeug

|           |                            |
|-----------|----------------------------|
| Version   | STANDARD                   |
| Type      | TL                         |
| Tyre Size | 275/80 R 20<br>(10.5 R 20) |
| LI/SS     | 134 K                      |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Overall Width (mm)         | 270             |
| Overall Diameter (mm)      | 955             |
| Static Loaded Radius (mm)  | 443             |
| Rolling Circumference (mm) | 2913            |
| Rim Rec                    | W9              |
| Rim Alt                    | 9               |
| ECE                        | E11-54R-0020628 |

## Load capacity (Kg)

| km/h / bar | 5.20 |
|------------|------|
| 110        | 2120 |

Printed on 27.04.2024 18:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..