

MULTIMAX MT 518 - Technische Daten



Description

MULTIMAX MT 518 wurde speziell für Militär-LKWs entworfen. Der Reifen mit Blockprofil und Stahlbändern zeichnet sich durch hohe Durchstichfestigkeit sowie erstklassige Stabilität aus. Ferner widersteht MULTIMAX MT 518 hohen Geschwindigkeiten und gewährleistet einen verlängerten Reifenlebenszyklus.

UM

US Standard

Construction

 RADIAL

Machinery

Industrie: Militärfahrzeug

| | |
|-----------|------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 36 X 12.5 R 16.5 |
| LI/SS | 129 N |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94039517 |
| Section Width (inch) | 12.4 |
| Overall Diameter (inch) | 35.5 |
| Static Loaded Radius (inch) | 16.5 |
| Rolling Circumference (inch) | 108.6 |
| Rim Rec | 9.75 |
| ECE | E11-54R-0017917 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 65 |
| 85 | 4080 |

Printed on 26.04.2024 05:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..