

PAC MASTER - Technische Daten



Description

PAC MASTER ist ein Diagonalreifen für Straßenwalzen, der hohe Stabilität bietet und einen verlängerten Produktlebenszyklus sichert. Der Reifen ist aus einer speziellen Gummimischung hergestellt, die besondere Hitzebeständigkeit verleiht.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Walze

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

Dimensions International Standard

Ply Rating	12
Section Width (mm)	275
Overall Diameter (mm)	1016
Static Loaded Radius (mm)	471
Rolling Circumference (mm)	3107
Rim Rec	7.0
Rim Alt	7.5
ECE	E11-106R-005358

Load capacity (Kg)

km/h / bar	6.25
10	4000
15	3150

Printed on 19.04.2024 18:00

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..