

PAC MASTER - Technische Daten



Description

PAC MASTER ist ein Diagonalreifen für Straßenwalzen, der hohe Stabilität bietet und einen verlängerten Produktlebenszyklus sichert. Der Reifen ist aus einer speziellen Gummimischung hergestellt, die besondere Hitzebeständigkeit verleiht.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Walze

Version	STANDARD
Type	TT
Tyre Size	9.00 - 20

Dimensions US Standard

Usa code	94002665
Ply Rating	16
Section Width (inch)	10.8
Overall Diameter (inch)	40
Static Loaded Radius (inch)	18.5
Rolling Circumference (inch)	122.3
Rim Rec	7.0
Rim Alt	7.5
ECE	E11-106R-005360

Load capacity (lbs)

mph / psi	120
5	10500
10	8270

Printed on 19.04.2024 21:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..