

## PL 801 - Technische Daten



### Description

PL 801 wurde speziell für die Heuernte mit Rotorschwadern/Zettwendern sowie für Logistikanwendungen mit Gabelstaplern entworfen. Er zeichnet sich durch ausgezeichnete Stabilität sowie hohe Schnitt- und Reißfestigkeit aus. PL 801 gewährleistet ein verlängertes Reifenleben.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Mährescher • Rotorschwader •  
Gabelstapler  
Industrie: Gabelstapler

Version	STANDARD
Type	TT
Tyre Size	21 X 8 - 9 (200/75 - 9)

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	200
Overall Diameter (mm)	535
Rim Rec	6.00 E
Rim Alt	7.00 E
ECE	E11-106R-003643

## Load capacity (Kg)

	km/h / bar	9.00
25 LOAD WHEEL		2535
25 STEER WHEEL		1950
10 OTHER VEHICLES		2535
25 OTHER VEHICLES		1950
STATIC SIDE LOADER		2945

Printed on 20.04.2024 00:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..