

PL 801 - Technische Daten



Description

PL 801 wurde speziell für die Heuernte mit Rotorschwadern/Zettwendern sowie für Logistikanwendungen mit Gabelstaplern entworfen. Er zeichnet sich durch ausgezeichnete Stabilität sowie hohe Schnitt- und Reißfestigkeit aus. PL 801 gewährleistet ein verlängertes Reifenleben.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Mährescher • Rotorschwader •
Gabelstapler
Industrie: Gabelstapler

Version	STANDARD
Type	TT
Tyre Size	23 X 5 (23 X 5 (- 13))

Dimensions US Standard

Usa code	94007028
Ply Rating	6
Section Width (inch)	6.1
Overall Diameter (inch)	25.2
Rim Rec	3.75 P

Load capacity (lbs)

	mph / psi	77
15 LOAD WHEEL		3295
15 STEER WHEEL		2535
5 OTHER VEHICLES		3295
15 OTHER VEHICLES		2535
STATIC SIDE LOADER		3825

Printed on 19.04.2024 17:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..