

PL 801 - Technische Daten



Description

PL 801 wurde speziell für die Heuernte mit Rotorschwadern/Zettwendern sowie für Logistikanwendungen mit Gabelstaplern entworfen. Er zeichnet sich durch ausgezeichnete Stabilität sowie hohe Schnitt- und Reißfestigkeit aus. PL 801 gewährleistet ein verlängertes Reifenleben.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Mähdrescher • Rotorschwader •
Gabelstapler
Industrie: Gabelstapler

Version	STANDARD
Type	TT
Tyre Size	6.50 - 10

Dimensions International Standard

Ply Rating	10
Section Width (mm)	185
Overall Diameter (mm)	595
Rim Rec	5.00 F
Rim Alt	5.50 F
ECE	E11-106R-003566

Load capacity (Kg)

	km/h / bar	7.80
25 LOAD WHEEL		1950
25 STEER WHEEL		1500
10 OTHER VEHICLES		1950
25 OTHER VEHICLES		1500
STATIC SIDE LOADER		2265

Printed on 19.04.2024 19:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..