

## PL 846 - Technische Daten



### Description

PL 846 wurde speziell für landwirtschaftliche Geräte zur Bodenbearbeitung entworfen. Er zeichnet sich durch ausgezeichnete Stabilität und erstklassige Traktion sowie hohe Schnitt- und Reißfestigkeit aus. PL 846 ist der ideale Reifen auf felsigem Gelände.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Landwirtschaftliche Geräte

Version	STANDARD
Type	TT
Tyre Size	6.00 - 9

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	160
Overall Diameter (mm)	540
Rim Rec	4.00 E

## Load capacity (Kg)

km/h / bar	8.50
25	1320

Printed on 26.04.2024 20:08

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..