

## PORT KING CLASSIC - Technische Daten



### Description

PORT KING CLASSIC ist ein BKT Hafenreifen der letzten Generation, der speziell für Fahrzeuge im Containerumschlag entwickelt wurde. Der Reifen bietet maximale Effizienz im Einsatz sowie ausgezeichnete Stabilität im Hebemodus. Dank seiner robusten Nylonkarkasse zeichnet sich PORT KING CLASSIC durch höhere Tragfähigkeit bei gleichzeitiger Minimierung des Risikos von Durchbrüchen, Rissen und Durchstößen aus. Die neue, verschleißfeste Mischung wurde zur Gewährleistung eines verlängerten Produktlebenszyklus neben bester Kapitalrendite entwickelt.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Reach-Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 - 25

## Dimensions International Standard

Ply Rating	40
Overall Width (mm)	528
Overall Diameter (mm)	1675
Static Loaded Radius (mm)	765
Rolling Circumference (mm)	4955
Rim Rec	13.00 /2.5
Rim Alt	15.00/2.5
TRA Code	IND4

## Load capacity (Kg)

km/h / bar	10.00
10	22950

Printed on 25.04.2024 06:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..