

PORT KING PLUS - Datenblatt



Description

PORT KING PLUS wurde speziell für Reach-Stacker in Transport-/intermodalen Logistikanwendungen entwickelt. Die tiefe Lauffläche mit starken Stollen ist aus einer speziellen Gummimischung hergestellt, die einen verlängerten Produktlebenszyklus des Reifens bietet. Eine Ausführung mit einer gegenüber Rissen im Laufflächenprofil besonders widerstandsfähigen Gummimischung ("GCRC" groove crack resistant compound), ist ebenfalls erhältlich.

UM

US Standard

Construction

✚ BIAS

Machinery

Industrie: Reach-Stacker

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
18.00 - 25	GCRC	94026593	IND4	40	13.00 /2.5	15.00/2.5	20.8	65.9	30.1	195.1	TL

Printed on 27.04.2024 11:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..