

## PORTMAX PM 90 - Technische Daten



### Description

PORTMAX PM 90 wurde speziell für Reach-Stacker in unterschiedlichen Anwendungen einschließlich industrielle Materialbewegung und Stahlwerke entwickelt wurden. Die besondere antistatische Laufflächenmischung gewährleistet besondere Hitzebeständigkeit sowie einen verlängerten Lebenszyklus. PORTMAX PM 90 bietet einen reduzierten Rollwiderstand, der sich in Kraftstoffersparnis zeigt.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrie: Reach-Stacker

Version	INDUSTRIAL
Type	TL
Tyre Size	18.00 R 33
LI/SS	214 A5

## Dimensions US Standard

Usa code	94057184
Overall Width (inch)	19.1
Overall Diameter (inch)	72.6
Static Loaded Radius (inch)	33.7
Rolling Circumference (inch)	221.4
Rim Rec	13.00/2.50
Rim Alt	13.00/2.50 IF
Star Rating	***

## Load capacity (lbs)

mph / psi	145
15	46700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11.02.2025 12:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..