

## PORTMAX PM 93 PLUS - Technische Daten



### Description

PORTMAX PM 93 PLUS wurde für Straddle Carrier zum Einsatz im Hafenumschlag konzipiert. Der All-Steel-Radialreifen mit mehrlagigen Stahlbändern weist eine erhöhte Stabilität und Beständigkeit auf. Die spezielle antistatische Laufflächenmischung gewährleistet hervorragende Hitzebeständigkeit und ein verlängertes Reifenleben. PORTMAX PM 93 PLUS bietet einen reduzierten Rollwiderstand für mehr Kraftstoffersparnis.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industrie: Portalhubwagen

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 R 25
LI/SS	200 A5

## Dimensions US Standard

Usa code	94047680
Overall Width (inch)	16.7
Overall Diameter (inch)	59.6
Static Loaded Radius (inch)	27.5
Rolling Circumference (inch)	180.4
Rim Rec	11.25/2.0
Star Rating	**

## Load capacity (lbs)

mph / psi	145
15	30900

Printed on 09.05.2024 04:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..