

## POWER RIB F2 - Technische Daten



### Description

POWER RIB F2 wurde speziell für 2WD Traktoren zur Bodenbearbeitung entworfen. Dieser Reifen zum vorwiegenden Einsatz auf dem Feld eignet sich besonders für alle Arbeiten, die hervorragendes Lenkverhalten erfordern.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: 2WD-Traktor

Version	STANDARD
Type	TL
Tyre Size	11L - 15 SL
LI/SS	110 A6

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	279
Overall Diameter (mm)	813
Static Loaded Radius (mm)	374
Rolling Circumference (mm)	2423
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-004652
TRA Code	F2

## Load capacity (Kg)

km/h / bar	3.00
30	1060

Printed on 15.08.2024 10:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..