

POWER TRAX HD (FL) - Technische Daten



Description

Der POWER TRAX HD ist ein hochwertiger Diagonalreifen, der speziell für Gabelstaplergeräte in industriellen Anwendungen entwickelt wurde. Die tiefe Lauffläche, die extra dicke Seitenwand und die zähe Karkasse bieten eine außergewöhnliche Beständigkeit und minimieren das Risiko von Reifenpannen und Unfallschäden. Der Reifen weist eine ausgezeichnete Schnitt-, Span- und Reißfestigkeit auf, die für raue und harte Betonoberflächen geeignet ist. Der speziell konstruierte Felgenschutz gewährleistet Schutz gegen Flachstellen und Radschäden im Felgenhornbereich.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Gabelstapler

Version	STANDARD
Type	TT
Tyre Size	10.00L - 15 (36 X 11 - 15)

Dimensions International Standard

Ply Rating	24
Section Width (mm)	285
Overall Diameter (mm)	918
Rim Rec	7.50 BD
Rim Alt	7.5

Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	6240
25 STEER WHEEL	4800
10 OTHER VEHICLES	6240
25 OTHER VEHICLES	4800
STATIC SIDE LOADER	7250

Printed on 20.04.2024 07:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..