

POWER TRAX HD SMOOTH - Technische Daten



Description

POWER TRAX HD SMOOTH ist ein Diagonalreifen, der speziell zum Einsatz im Hafenumschlag und Untertagebau entwickelt wurde. Der besondere Flankenschutz und das solide Reifenprofil schützen vor Schnitten und Stichen, den am weitesten verbreiteten Gefahren in anspruchsvollen Umgebungen. Wann immer es darum geht, schwere Ladungen zu bewegen, Power Trax HD Smooth ist der ideale Reifen für Ihren Bedarf.

UM

International Standard

Construction

 BIAS

Machinery

Industrie: Containerstapler • Gabelstapler
OTR: Untertagefahrzeug

Version	STANDARD
Type	TT
Tyre Size	12.00 - 20

Dimensions International Standard

Ply Rating	20
Section Width (mm)	320
Overall Diameter (mm)	1150
Rim Rec	8.50
Rim Alt	9.0
ECE	E11-106R-005561

Load capacity (Kg)

km/h / bar	10.00
25 LOAD WHEEL	9230
25 STEER WHEEL	7100
10 OTHER VEHICLES	9230
25 OTHER VEHICLES	7100
STATIC SIDE LOADER	10720

Printed on 22.02.2024 20:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..