

POWER TRAX HD (SS) - Datenblatt



Description

Der Premiumreifen POWER TRAX HD ist speziell für Geräte im Hafen- und Untertagebergbau konzipiert. Sein tiefes Profil, die extra dicke Seitenwand und die zähe Karkasse bieten eine außergewöhnliche Beständigkeit und minimieren das Risiko von Reifenpannen und Unfallschäden. Der Reifen zeichnet sich durch eine hervorragende Schnitt- und Spanbeständigkeit aus, die besonders für raue und harte Oberflächen geeignet ist. Der speziell konstruierte Felgenschutz gewährleistet Schutz vor Pannen und Radschäden im Bereich des Felgenhorns.

UM

US Standard

Construction

 BIAS

Machinery

Industrie: Skid-Steer-Lader

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10 - 16.5	IMPLEMENT	94055777	120 A8	10	8.25		10.6	31.1	14.2	91.8	TL	E11-106R-003531
10 - 16.5	STANDARD	94017300		10	8.25		10.6	31.1	14.2	91.8	TL	
12 - 16.5	STANDARD	94017331		10	9.75		12.8	34.1	15.4	100.5	TL	
12 - 16.5	STANDARD	94017355		12	9.75		12.8	34.1	15.4	100.5	TL	E11-106R-005557
12 - 16.5	STANDARD	94017393		14	9.75		12.8	34.1	15.4	100.5	TL	E11-106R-005562

Printed on 25.04.2024 10:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..