

## POWER TRAX - Technische Daten



### Description

POWER TRAX ist ein Premium-Reifen, der speziell für den schweren Einsatz auf Hafentrailern, Leercontainerumschlagmaschinen oder ECH- und Bergbaumaschinen unter Tage entwickelt wurde. Das tiefe Profil und die robuste Karkasse sorgen für außergewöhnliche Haltbarkeit und minimieren das Risiko von Reifenpannen und Unfallschäden. Der POWER TRAX ist dank seiner einzigartigen Laufflächenmischung, die eine hervorragende Beständigkeit gegen Schnitte und Abplatzungen bietet, der ideale Reifen für harte und schwierige Einsätze.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrie: Leercontainerstapler  
OTR: Untertagefahrzeug

|           |             |
|-----------|-------------|
| Version   | STANDARD    |
| Type      | TL          |
| Tyre Size | 355/65 - 15 |
| LI/SS     | 170 A5      |

## Dimensions International Standard

|                            |      |
|----------------------------|------|
| Ply Rating                 | 24   |
| Section Width (mm)         | 335  |
| Overall Diameter (mm)      | 830  |
| Static Loaded Radius (mm)  | 380  |
| Rolling Circumference (mm) | 2530 |
| Rim Rec                    | 9.75 |
| Tread Depth                | 28   |

## Load capacity (Kg)

|                    |       |
|--------------------|-------|
| km/h / bar         | 10.00 |
| 25 LOAD WHEEL      | 7800  |
| 25 STEER WHEEL     | 6000  |
| 10 OTHER VEHICLES  | 7800  |
| 25 OTHER VEHICLES  | 6000  |
| STATIC SIDE LOADER | 9060  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21.05.2025 21:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..