

PUDDLE SPECIAL (A) - Technische Daten



Description

PUDDLE SPECIAL ist ein R-2 Landwirtschaftsreifen, der speziell zum Einsatz auf Reisfeldern entwickelt wurde. Das besonders tiefe Laufflächenmuster sowie die spezielle Anordnung der Stollen verleihen hervorragende Haftung auch auf nassem und weichem Boden. Die breite Mittelrippe verleiht bessere Anpassungsfähigkeit im Straßeneinsatz, was sich in hervorragenden Leistungen zeigt. Darüber hinaus weist PUDDLE SPECIAL erstklassige Selbstreinigungseigenschaften und ausgezeichnete Beständigkeit auf.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Traktor

Version	STANDARD
Type	TT
Tyre Size	11 - 32
LI/SS	111 A2

Dimensions International Standard

Ply Rating	6
Section Width (mm)	305
Overall Diameter (mm)	1465
Static Loaded Radius (mm)	702
Rolling Circumference (mm)	4384
Rim Rec	W 10
Rim Alt	W 9
ECE	E11-106R-004096
TRA Code	R2+

Load capacity (Kg)

km/h / bar	1.60
10	1090

Printed on 23.04.2024 04:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..