

## RIB 324 - Technische Daten



### Description

RIB 324 wurde mit einem speziellen Blockmuster der Lauffläche und einer breiten Aufstandsfläche entwickelt, um hervorragende Stabilität und Flotationseigenschaften auf lockerer Erde und Sandboden zu gewährleisten. Die robuste Nylonkarkasse und Seitenwand sowie die spezielle Gummimischung der Lauffläche stehen für erstklassige Durchstich- und Verschleißfestigkeit sowie höhere Tragfähigkeit.

### UM

US Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Landwirtschaftliche Geräte  
Industrie: Anhänger

Version	STANDARD
Type	TL
Tyre Size	66 X 44.00 - 25

## Dimensions US Standard

Usa code	94064274
Ply Rating	20
Section Width (inch)	43.7
Overall Diameter (inch)	66.9
Rim Rec	36.0 TH

## Load capacity (lbs)

	mph / psi	50
	30	16090

Printed on 23.04.2024 17:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..