

RIB 774 (A) - Technische Daten



Description

RIB 774 (A) ist ein Niederquerschnittsreifen für landwirtschaftliche Geräte, der hohe Tragfähigkeit kombiniert mit einem langen Produktlebenszyklus bietet. Der Reifen eignet sich vortrefflich für die Heuernte und Transportanwendungen mit Heupressen und Anhängern.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher • Anhänger

Version	HD
Type	TT
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	106 A8

Dimensions US Standard

Usa code	94053216
Ply Rating	10
Section Width (inch)	8.3
Overall Diameter (inch)	24
Static Loaded Radius (inch)	11.3
Rolling Circumference (inch)	74.3
Rim Rec	AG 6.75
ECE	E11-106R-005259

Load capacity (lbs)

mph / psi	73
5 FR	2930
15 FR	2490
20 FR	2350
25 FR	2090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11.02.2025 16:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..