

RIB 774 (A) - Technische Daten



Description

RIB 774 (A) ist ein Niederquerschnittsreifen für landwirtschaftliche Geräte, der hohe Tragfähigkeit kombiniert mit einem langen Produktlebenszyklus bietet. Der Reifen eignet sich vortrefflich für die Heuernte und Transportanwendungen mit Heupressen und Anhängern.

UM

US Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher • Anhänger

Version	STANDARD
Type	TL
Tyre Size	250/65 - 14.5
LI/SS FREE ROLLING	124 A8

Dimensions US Standard

Usa code	94027255
Ply Rating	14
Section Width (inch)	10
Overall Diameter (inch)	27.2
Static Loaded Radius (inch)	11.9
Rolling Circumference (inch)	77.9
Rim Rec	AG 8.00
Rim Alt	6.75
ECE	E11-106R-003374

Load capacity (lbs)

mph / psi	80
5 FR	4940
15 FR	4200
20 FR	3950
25 FR	3530

Printed on 16.04.2024 23:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..