

RIB 774 (B) - Technische Daten



Description

RIB 774 (B) ist ein Niederquerschnittsreifen für landwirtschaftliche Geräte - ideal für die moderne Landwirtschaft. Der Reifen eignet sich vortrefflich für Anwendungen auf und abseits der Straße mit landwirtschaftlichen Geräten und Anhängern. Er bietet hervorragende Tragfähigkeit und ein langes Reifenleben. Es gibt auch eine „HD“-Version für schwere Einsatzbedingungen.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Landwirtschaftliche Geräte • Anhänger
Industrie: Anhänger

| | |
|--------------------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 15.0/55 - 17 |
| LI/SS FREE ROLLING | 134 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 10 |
| Section Width (mm) | 391 |
| Overall Diameter (mm) | 850 |
| Static Loaded Radius (mm) | 377 |
| Rolling Circumference (mm) | 2490 |
| Rim Rec | 13.00 |
| Rim Alt | 13 |
| ECE | E11-106R-004309 |

Load capacity (Kg)

| km/h / bar | 2.60 |
|------------|------|
| 10 FR | 2970 |
| 25 FR | 2525 |
| 30 FR | 2375 |
| 40 FR | 2120 |

Printed on 26.04.2024 10:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..