

RIB 774 (C) - Technische Daten



Description

RIB 774 (C) ist ein Niederquerschnitts- und Schmalreifen für landwirtschaftliche Geräte. Der Reifen ist ideal für Transportanwendungen mit Heupressen und Anhängern auf und abseits der Straße. Er bietet hervorragende Tragfähigkeit und ein langes Reifenleben.

UM

International Standard

Construction

 BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher • Anhänger

Version	STANDARD
Type	TL
Tyre Size	215/75 - 17.5
LI/SS FREE ROLLING	134 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	220
Overall Diameter (mm)	775
Static Loaded Radius (mm)	360
Rolling Circumference (mm)	2310
Rim Rec	6.75
ECE	E11-106R-004590

Load capacity (Kg)

	km/h / bar	6.90
	10 FR	2970
	25 FR	2525
	30 FR	2375
	40 FR	2120

Printed on 19.04.2024 03:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..