

## RIB 774 (C) - Technische Daten



### Description

RIB 774 (C) ist ein Niederquerschnitts- und Schmalreifen für landwirtschaftliche Geräte. Der Reifen ist ideal für Transportanwendungen mit Heupressen und Anhängern auf und abseits der Straße. Er bietet hervorragende Tragfähigkeit und ein langes Reifenleben.

### UM

International Standard

### Construction

 BIAS

### Machinery

Landwirtschaft: Heupresse • Mähdrescher • Anhänger

Version	STANDARD
Type	TL
Tyre Size	225/75 - 17.5
LI/SS FREE ROLLING	139 A8

## Dimensions International Standard

<b>Ply Rating</b>	16
<b>Section Width (mm)</b>	220
<b>Overall Diameter (mm)</b>	775
<b>Static Loaded Radius (mm)</b>	360
<b>Rolling Circumference (mm)</b>	2310
<b>Rim Rec</b>	6.75
<b>ECE</b>	E11-106R-004591

## Load capacity (Kg)

	km/h / bar	9.00
	10 FR	3710
	25 FR	3155
	30 FR	2970
	40 FR	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22.03.2025 12:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..