

RIB 900 - Technische Daten



Description

RIB 900 eignet sich für Transport, Bodenbearbeitung und Heuernte mit Anhängern, landwirtschaftlichen Geräten und Heupressen. Er bietet ausgezeichnete Tragfähigkeit sowie ein langes Reifenleben.

UM

US Standard

Construction

❖ BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher •
Landwirtschaftliche Geräte • Anhänger

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	145 A8

Dimensions US Standard

Usa code	94026173
Ply Rating	14
Section Width (inch)	15.9
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	15
Rolling Circumference (inch)	100.9
Rim Rec	AG 13.00
ECE	E4-106R-001551

Load capacity (lbs)

mph / psi	52
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390

Printed on 23.04.2024 13:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..