

RIB 900 - Technische Daten



Description

RIB 900 eignet sich für Transport, Bodenbearbeitung und Heuernte mit Anhängern, landwirtschaftlichen Geräten und Heupressen. Er bietet ausgezeichnete Tragfähigkeit sowie ein langes Reifenleben.

UM

International Standard

Construction

✚ BIAS

Machinery

Landwirtschaft: Heupresse • Mähdrescher •
Landwirtschaftliche Geräte • Anhänger

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS FREE ROLLING	147 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	405
Overall Diameter (mm)	875
Static Loaded Radius (mm)	380
Rolling Circumference (mm)	2564
Rim Rec	AG 13.00
ECE	E4-106R-001548

Load capacity (Kg)

	km/h / bar	4.00
	10 FR	4305
	25 FR	3660
	30 FR	3445
	40 FR	3075

Printed on 23.04.2024 08:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..