RIB F3 - Technische Daten

Description

RIB F3 ist ein Reifen zum vorwiegenden Einsatz auf dem Feld mit 2WD Traktoren bei der Bodenbearbeitung und zum Transport. Einige Größen sind auch für Transportanwendungen mit landwirtschaftlichen Geräten und Anhängern geeignet. Der RIB F3 Reifen ist der ideale Partner für alle Arbeiten, die einen hohen Level an Manövrierbarkeit verlangen. Die harte Gummimischung verleiht ausgezeichnete Beständigkeit und Widerstandsfähigkeit gegen Stoppeln.

UM

International Standard

Construction

BIAS

Machinery

Landwirtschaft: 2WD-Traktor • Anhänger

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16
LI/SS	120 A6/ 112 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	245
Overall Diameter (mm)	878
Static Loaded Radius (mm)	387
Rolling Circumference (mm)	2573
Rim Rec	W 8
Rim Alt	6.00 F ; W 7 ; W 8 L
ECE	E11-106R-004592
TRA Code	F3

Load capacity (Kg)

km/h / bar	4.70
30	1400
40	1120

Printed on 20.04.2024 13:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..